



## 96649333 CHARTOR HEAD LF LED800-840 LUC S/BLACK

AS/NZS 60598	IP44	IK09		
-----------------	------	------	---	---

### Chartor


A timeless bollard offering modest visual guidance and comfortable light with low glare. Head: die-cast aluminium, powder coated black (Other colours available upon request). Diffuser: semi-opal anti-UV polycarbonate. Lenses: clear polycarbonate. Class I electrical, IP44, Impact strength: IK09. Low upward component limiting upward stray light for improved visual comfort.

Electronic, fixed output control gear for LED. Complete with 4000K LED

Dimensions: Ø140 x 230 mm  
 Luminaire input power: 27.5 W  
 Weight: 2.3 kg



TLA\_CHAR\_F\_HEAD\_BK.jpg



TLA\_CHAR\_M\_HEAD.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

**Chartor**

**96649333 CHARTOR HEAD LF LED800-840 LUC S/BLACK**

**THORN**