

Contrast

96633440 CONT3 4L50-822-40 MB NG IN ANT

| | | | | | | | |
|----------------|--|------|------|--|--|--|---------------------------|
| ISO 9223 C5 | | IP66 | IK08 | | | | T _a -20 +35 |
|----------------|--|------|------|--|--|--|---------------------------|


Contrast

A small architectural Bracket mounted LED floodlight with LEDs driven at 500mA and a medium beam distribution. .. Pre-wired with IP66 connector, gear box to be ordered separately. Class II electrical (this product is not earthed), IP66, IK08. Body: die-cast aluminium (EN AC-44300), powder coated, textured anthracite (close to RAL7043). Compatible with coastal environments. Glass: tempered, 5mm thick. Gasket: EPDM. Screws: geomet. Complete with 2200-4000K balanced white LEDs

Dimensions: Ø83 x 103 mm
 Luminaire input power: 7 W
 Luminaire luminous flux: 347 lm
 Luminaire efficacy: 50 lm/W
 Weight: 0.9 kg



TLG_CON3_F_XS.jpg



TLG_CONL_M_4L.wmf

This product contains a light source of energy efficiency class F.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Contrast

96633440 CONT3 4L50-822-40 MB NG IN ANT

THORN