

## IQ Beam

96634277 IQ BEAM 3000-840 MPT-F HF Q600

IEC EN 60598-1 RG 1		IP20	IK03				650 °C	T <sub>a</sub> -20 +40
---------------------------	--	------	------	--	--	--	--------	---------------------------

### IQ Beam

A linear optic, recessed modular LED luminaire for exposed T, plasterboard and concealed grid ceilings. Fixed output, LED driver. Class I electrical, IP20, Impact strength: IK03. Body: white painted steel. Diffuser: micro prism structure acrylic with diffusing foil. Suitable for lay-in installation, pull up installation optional. Complete with 4000K LED.

Dimensions: 597 x 597 x 60 mm  
 Luminaire input power: 24.7 W  
 Luminaire luminous flux: 3000 lm  
 Luminaire efficacy: 121 lm/W  
 Weight: 4.14 kg



TLG\_IQBM\_F\_pers\_B.jpg



TLG\_IQBM\_M\_LDQ.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

# **IQ Beam**

**96634277 IQ BEAM 3000-840 MPT-F HF Q600**

**THORN**