

Punch

96630502 <PUNCH 3 ASYM MSP 2200-830 L12 HF

| | | | | | | | | | | |
|----------|------|------|--|--|--|--|--|--|-------|-------------------------|
| UK CA | IP20 | IK03 | | | | | | | 650°C | T _a 0 +25 |
|----------|------|------|--|--|--|--|--|--|-------|-------------------------|

Punch

A slim, suspended luminaire with asymmetrical distribution. Fixed output LED driver. Body: steel sheet, powder coated white (close to RAL9016). Endcaps: steel sheet powder coated white (close to RAL9016). Louvre: glossy aluminium, double parabolic. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 3000K LED. Suspension kit to be ordered separately

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1180 x 116 x 44 mm
 Luminaire input power: 16 W
 Luminaire luminous flux: 2050 lm
 Luminaire efficacy: 128 lm/W
 Weight: 3.5 kg



TLG_PNCH_F_ASYM.jpg



TLG_PNC3_M_LDASY.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Punch

96630502 <PUNCH 3 ASYM MSP 2200-830 L12 HF

THORN