

## Indilouver Pro

96650815 INDI PRO LED3700-940 12x3 AH FP

|      |      |      |  |  |        |                           |
|------|------|------|--|--|--------|---------------------------|
| RoHS | IP20 | IK02 |  |  | 750 °C | T <sub>a</sub> -20<br>+40 |
|------|------|------|--|--|--------|---------------------------|

### Indilouver Pro

A stylish ceiling recessed LED luminaire. Fixed output LED driver. Class I electrical, IP20, Impact strength: IK02. Body: white painted steel, with option for concealed air return. Diffuser: 2mm thick, clear PMMA, linear profile. Baffle: aluminium extrusion. Fitted with flex and plug. Complete with 4000K LED, COI approved.

Dimensions: 1195 x 295 x 76 mm  
 Luminaire input power: 35 W  
 Luminaire luminous flux: 3982 lm  
 Luminaire efficacy: 114 lm/W  
 Weight: 5.8 kg



TLG\_INPR\_F\_WH.jpg



TLG\_INPR\_M\_M-L.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.