

Punch

96635405 PUNCH 3 LRO MSP 5500-840 L12 HFIX E3D

UK CA	IP20	IK03	⊕	⚡	⚙️	⚙️	⚙️	650°C	T _a 0 +25
----------	------	------	---	---	----	----	----	-------	-------------------------

Punch


A slim, suspended luminaire with direct/indirect distribution. DALI dimmable Electronic, with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: steel sheet, powder coated white (close to RAL9016). Endcaps: steel sheet powder coated white (close to RAL9016). Light guided via backlit multilayer PMMA LRO luminance reducing optic with UGR <19, closed optical system to prevent damage from electrostatic discharge, ideal for schools and offices. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 4000K LED.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1262 x 162 x 50 mm
 Luminaire input power: 42.3 W
 Luminaire luminous flux: 5383 lm
 Luminaire efficacy: 127 lm/W
 Weight: 6.2 kg



TLG_PNCH_F_LRO_suspended_on_PDB.jpg



TLG_PNC3_M_PLEXD.wmf

This product contains light sources of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Punch

96635405 PUNCH 3 LRO MSP 5500-840 L12 HFIX E3D

THORN