

# Novaline Style

# THORN

## 96635526 NOVS S 1900-840 DI HFI E3D WH

|                           |      |          |      |   |         |      |  |  |  |  |       |                         |
|---------------------------|------|----------|------|---|---------|------|--|--|--|--|-------|-------------------------|
| IEC EN<br>60598-1<br>RG 1 | RoHS | UK<br>CA | IP54 | D | halogen | IK08 |  |  |  |  | 850°C | T <sub>a</sub> 0<br>+25 |
|---------------------------|------|----------|------|---|---------|------|--|--|--|--|-------|-------------------------|

### Novaline Style

Decorative circular luminaire with small body. Low indirect component for wall and ceiling illumination. Electronic, DALI dimmable with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Aesthetic trim of the luminaire made of polycarbonate in white. Diffuser: opal polycarbonate. Class II electrical (this product is not earthed), IP54. Complete with 4000K LED.

Dimensions: Ø320 x 69 mm  
Luminaire input power: 13.2 W  
Luminaire luminous flux: 1900 lm  
Luminaire efficacy: 144 lm/W  
Weight: 1.96 kg



TLG\_NOVS\_F\_3WH.jpg



TLG\_NOVS\_M\_LD300.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting