

Indilouver Pro

96651676 INDI PRO LED2700-940 6X6 AH FP

RoHS	IP20	IK02			750 °C	T _a -20 +40
------	------	------	--	--	--------	---------------------------


Indilouver Pro

A stylish ceiling recessed LED luminaire. Fixed output LED driver. Class I electrical, IP20, Impact strength: IK02. Body: white painted steel, with option for concealed air return. Diffuser: 2mm thick, clear PMMA, linear profile. Baffle: aluminium extrusion. Fitted with flex and plug. Complete with 4000K LED, COI approved.

Dimensions: 595 x 595 x 106 mm
 Luminaire input power: 24.6 W
 Luminaire luminous flux: 2802 lm
 Luminaire efficacy: 114 lm/W
 Weight: 5.5 kg



TLG_INPR_F_WH.jpg



TLG_INPR_M_Q.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
 © Thorn Lighting

Indilouver Pro

96651676 INDI PRO LED2700-940 6X6 AH FP

THORN