

## Punch

96635718 PUNCH 3 LV MSC 6000-940 L15 HFIX

|          |      |      |  |  |  |  |       |                         |
|----------|------|------|--|--|--|--|-------|-------------------------|
| UK<br>CA | IP20 | IK03 |  |  |  |  | 650°C | T <sub>a</sub> 0<br>+25 |
|----------|------|------|--|--|--|--|-------|-------------------------|

### Punch

A slim, surface mounted luminaire with direct distribution. DALI dimmable Electronic,. Body: steel sheet, powder coated white (close to RAL9016). Endcaps: steel sheet powder coated white (close to RAL9016). Louvre: glossy aluminium,. Class I electrical, IP20, Impact strength: IK03. Electrical connection via piano key terminal block. Complete with 4000K LED.

Can be used as a suspended direct only luminaire when combined with Y-Suspension connector and suspension kit (to be ordered separately 22171581 & 22171349).

Dimensions: 1581 x 162 x 56 mm  
 Luminaire input power: 44 W  
 Luminaire luminous flux: 5910 lm  
 Luminaire efficacy: 134 lm/W  
 Weight: 3.8 kg



TLG\_PNCH\_F\_LOUVRE\_surface\_on.jpg



TLG\_PNC3\_M\_LV\_RESD.wmf

This product contains light sources of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.