

Candle Bollard

THORN

96679075 CN B 8L70 830 RSC CL2 MPL ANT

ISO 9223	C5	IP66	IK10				T _a 25	
----------	----	------	------	---	---	---	-------------------	--

Candle Bollard

Environmentally respectful bollard with limited upward lighting emission with 8 LEDs driven at 700mA with Radial symmetrical comfort light distribution. Fixed output LED driver. Class II electrical (this product is not earthed), IP66, IK10. Base: die-cast aluminium (EN AC-44300). Finish: powder coated aluminium, texturized anthracite (close to RAL7043). Diffuser: UV stabilised clear polycarbonate. Flange mounted. Complete with 3000K LED.

Dimensions: Ø234 x 1017 mm

Luminaire input power: 19 W

Weight: 7.95 kg

Scx: 0.06 m²

Luminaire efficacy: 91 lm/W



TLG_CNDB_F_MPL.jpg



TLG_CNDB_M_MPL.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Candle Bollard

96679075 CN B 8L70 830 RSC CL2 MPL ANT

THORN