

## Punch

96636016 PUNCH 3 LV MSP 5500-840 L12 HF

UK CA	IP20	IK03	⊕	⚡	⚙️	⚙️	⚙️	650°C	T <sub>a</sub> 0 +25
----------	------	------	---	---	----	----	----	-------	-------------------------

### Punch

A slim, suspended luminaire with direct/indirect distribution. fixed output control gear Electronic,. Body: steel sheet, powder coated white (close to RAL9016). Endcaps: steel sheet powder coated white (close to RAL9016). Louvre: glossy aluminium,. Class I electrical, IP20, Impact strength: IK03. Electrical connection via piano key terminal block. Complete with 4000K LED.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1301 x 162 x 56 mm  
 Luminaire input power: 39 W  
 Luminaire luminous flux: 5590 lm  
 Luminaire efficacy: 143 lm/W  
 Weight: 3.5 kg



TLG\_PNCH\_F\_LOUVRE\_recessed\_on.jpg



TLG\_PNC3\_M\_LV\_RESD.wmf

This product contains light sources of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.