
Isaro



96636154 IS S 24L35-730 NR CL2 WS0.3 M60 GY-S



Isaro


A discrete and flexible road and street lantern with durable high performance. Programmable LED driver, set for fixed output, driving 24 LEDs at 350mA. Body: small size, diecast aluminium (EN AC-44300), powder coated textured Light grey textured (150) - partly painted. Shaft: Light grey textured (150) - partly paintedunpainted. Cover: Extra White glass. Fixings: stainless steel with anti-galvanic treatment. narrow road optic, with Colour Rendering Index min.: 70, Correlated colour temperature*: 3000 Kelvin LEDs supplied. Class II electrical (this product is not earthed), Impact strength: IK08, IP66, Ta max.: 50°C. Supplied with Ø60mm spigot adaptor which can be fitted for post-top (0°/5°/10° tilt) or side-entry (-20°/-15°/-10°/-5°/0° tilt). Prewired with 0.3m, 1.5mm² H07RN-F cable.

Dimensions: 550 x 238 x 157 mm Luminaire input power: 25.8 W Luminaire luminous flux: 4012 lm Luminaire efficacy: 156 lm/W

Weight: 4 kg Scx: 0.041 m²



TLG ISLC F S ZU SR.jpg



TLG_ISLC_M_SMTP60.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Isaro



96636154 IS S 24L35-730 NR CL2 WS0.3 M60 GY-S