


Chalice 3

96108789 CHAL3 150 2000-840 EHF RSB IP65




Chalice 3

A highly efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver with DC functionality, adjustable 50-100%, NFC configurable. Loop in - loop out possible. Body: die-cast aluminium for highly efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam and additional ultrasonic welded clear polycarbonate cover IP65. Class II electrical (this product is not earthed), IP65_IP20. Complete with 4000K LED

Dimensions: Ø174 x 94 mm
 Luminaire input power: 16.9 W
 Luminaire luminous flux: 1910 lm
 Luminaire efficacy: 113 lm/W
 Weight: 0.71 kg



TLG_CHAL3_F_150_RSB_IP65.jpg



TLG_CHAL3_M_EHF150.wmf

This product contains a light source of energy efficiency class B.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.