Royal Elite



96652790 ROYAL ELITE LED4500-940 6X6 HFI FP




Royal Elite

Royal Elite is a high performance recessed LED modular luminaire. DALI dimmable LED driver. Body: white painted aluminium frame. Diffuser: High uniformity microprismatic, UGR<19. Suitable for Office, Retail and School applications. Class II electrical (this product is not earthed), IP44 IP20. Electrical connection: Fitted with flex and plug. Complete with 4000K LED, CRI95+, R9 80+, 2 Step MacAdam LED


This product has a Cyanosis Observation Index (COI) of less than 3.3, in accordance with AS/NZS 1680.2.5:1997 for hospitals and medical tasks.

Dimensions: 596 x 596 x 33 mm Luminaire input power: 41 W Luminaire luminous flux: 4895 lm Luminaire efficacy: 119 lm/W

Weight: 4 kg



TLG_RYLL_F_03.jpg



TLG_RYLL_M_66_LD.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.