

R2L2

THORN

96266400 R2L2 M 60L35 730 WS CL2 GY

ISO 9223 C5	ida LANK SKY APPROVED	IP66	IK08						T _a -25 +50
----------------	--------------------------	------	------	--	--	--	--	--	---------------------------


R2L2

A medium size LED road lighting lantern with 60 LEDs driven at 350mA with Wide Street optic. LED driver Programmable. Class II electrical (this product is not earthed), IP66, IK08. Housing: die-cast aluminium, powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. For lateral mounting to Ø34/42mm spigots an adaptor (59005840 R2L2 MA34/42 NPA) should be ordered separately. Complete with 3000K LED.

Dimensions: 880 x 370 x 155 mm
Luminaire input power: 63 W
Luminaire luminous flux: 9236 lm
Luminaire efficacy: 147 lm/W
Weight: 12.67 kg
Scx: 0.06 m²



TLG_R2L2_F_MPDB.jpg



TLG_R2L2_M_LDM.wmf

This product contains light sources of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

R2L2

96266400 R2L2 M 60L35 730 WS CL2 GY

THORN