

R2L2

96266763 R2L2 M 96L70 740 RC CL1 GY

ISO 9223 C5	IP66	IK08					T _a 25
----------------	------	------	--	--	--	--	-------------------

R2L2

A medium size LED road lighting lantern with 96 LEDs driven at 700mA with Road & Comfort optic. LED driver Programmable. Class I electrical, IP66, IK08. Housing: die-cast aluminium, powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. Complete with 4000K LED.

Dimensions: 880 x 370 x 155 mm
 Luminaire input power: 201 W
 Luminaire luminous flux: 30054 lm
 Luminaire efficacy: 150 lm/W
 Weight: 14.45 kg
 Scx: 0.06 m²



TLG_R2L2_F_MPDB.jpg



TLG_R2L2_M_LDM.wmf

This product contains light sources of energy efficiency classes D, E.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.