

# Omega Circular

THORN

96627777 OMEGA C LED2800-830 HFIX E3 R400

IP20	IK02						$T_a$ 0 +25
------	------	--	--	--	--	--	----------------

## Omega Circular

A versatile, circular edge lit panel for recessed mounting in a  $\text{\O}200\text{mm}$  cutout. Electronic, DALI dimmable control gear with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP20. Body: aluminium and steel,. Diffuser: acrylic opal. Complete with 3000K LED.

Dimensions:  $\text{\O}400 \times 55$  mm  
Luminaire input power: 33 W  
Luminaire luminous flux: 2649 lm  
Luminaire efficacy: 80 lm/W  
Weight: 3.3 kg



TLG\_OMGC\_F\_PDB.jpg



TLG\_OMGC\_M\_2800.wmf

This product contains a light source of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of  $25^\circ\text{C}$ .

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting