

96643089 CQ 60L70 740 RWT BS 3550 CL2 M60 GY-S

ISO 9223 C5			IP66	IK08					T <sub>a</sub> 25	
----------------	--	--	------	------	--	--	--	--	-------------------	--

## CiviTEQ

A large size LED road lighting lantern with 60 LEDs driven at 700mA with Wet Road optic. Electronic, fixed output control gear. Class II electrical (this product is not earthed), IP66, IK08. Housing: die-cast aluminium (EN AC-44300), Light grey 150 sanded textured (close to RAL9006). Enclosure: toughened flat glass. Screws: stainless steel, Ecolubric® treated. Supplied with Ø60mm spigot adaptor which can be fitted for post-top (0°/5°/10° tilt) or side-entry (-20°/-15°/-10°/-5°/0° tilt). Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Complete with 4000K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: 580 x 230 x 160 mm  
 Luminaire input power: 125 W  
 Luminaire luminous flux: 19424 lm  
 Luminaire efficacy: 155 lm/W  
 Weight: 9.6 kg  
 Scx: 0.115 m<sup>2</sup>



TLG\_CTEQ\_F\_LMTP72LEDPDB.jpg



TLG\_CETQ\_M\_L.wmf

This product contains light sources of energy efficiency classes D, E.

**CiviTEQ**

**96643089 CQ 60L70 740 RWT BS 3550 CL2 M60 GY-S**

**THORN**