

**96643190 CQ 36L50 740 EWC BS 3550 CL2 M60 GY-S**

ISO 9223 C5			IP66	IK08			T <sub>a</sub> 25	
----------------	--	--	------	------	--	--	-------------------	--


## CiviTEQ

A small size LED road lighting lantern with 36 LEDs driven at 500mA with Extra Wide Street & Comfort optic. Electronic, fixed output control gear. Class II electrical (this product is not earthed), IP66, IK08. Housing: die-cast aluminium (EN AC-44300), Light grey 150 sanded textured (close to RAL9006). Enclosure: toughened flat glass. Screws: stainless steel, Ecolubric® treated. Supplied with Ø60mm spigot adaptor which can be fitted for post-top (0°/5°/10° tilt) or side-entry (-20°/-15°/-10°/-5°/0° tilt). Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Complete with 4000K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: 390 x 230 x 133 mm  
 Luminaire input power: 55 W  
 Luminaire luminous flux: 8388 lm  
 Luminaire efficacy: 153 lm/W  
 Weight: 5.7 kg  
 Scx: 0.077 m²



TLG\_CTEQ\_F\_SMTP36LEDPDB.jpg



TLG\_CETQ\_M\_S.wmf

This product contains light sources of energy efficiency class E.

**CiviTEQ**

**96643190 CQ 36L50 740 EWC BS 3550 CL2 M60 GY-S**

**THORN**