

IQ Wave SP

THORN

96629279 IQ SUSP S LED4250-840 HF ML3 WH

IP20	IK05						650°C	T _a -20 +25
------	------	--	--	--	--	--	-------	---------------------------

IQ Wave SP

A lightweight, Suspended, LED luminaire with MV Tech optic. Electronic, fixed output control gear. Class I electrical, IP20, IK05. Body, diffuser, frame and endcaps: polycarbonate finished in white (close to RAL9016). Gear tray: pre-coated white steel. Fitted with 3 core cable of 2.5m length. Suspension wires included. Ceiling rose to be ordered separately. Complete with 4000K LED

Dimensions: 1140 x 210 x 70 mm

Luminaire input power: 40 W

Luminaire luminous flux: 4250 lm

Luminaire efficacy: 106 lm/W

weight: 4.3 kg



TLG_IQSU_F_SUS_PDB.jpg



TLG_IQSU_M_SUS.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

IQ Wave SP

96629279 IQ SUSP S LED4250-840 HF ML3 WH

THORN