

## 96636217 CQ 24L35-740 NR BP 3550 CL2 M60 GY-S

|                |   |   |      |      |   |   |                   |  |
|----------------|---|---|------|------|---|---|-------------------|--|
| ISO 9223<br>C5 |  |  | IP66 | IK08 |  |  | T <sub>a</sub> 25 |  |
|----------------|---|---|------|------|---|---|-------------------|--|

### CiviTEQ

A small size LED road lighting lantern with 24 LEDs driven at 350mA with Narrow Road optic. Electronic, fixed output control gear. Class II electrical (this product is not earthed), IP66, IK08. Housing: die-cast aluminium (EN AC-44300), Light grey 150 sanded textured (close to RAL9006). Enclosure: toughened flat glass. Screws: stainless steel, Ecolubric® treated. Supplied with Ø60mm spigot adaptor which can be fitted for post-top (0°/5°/10° tilt) or side-entry (-20°/-15°/-10°/-5°/0° tilt). BPxyz: Autonomous bi-power reduction (x: hours before midnight, y: hours after midnight, zz: reduction (%)) Complete with 4000K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode.

Dimensions: 390 x 230 x 133 mm  
 Luminaire input power: 25.7 W  
 Luminaire luminous flux: 4334 lm  
 Luminaire efficacy: 169 lm/W  
 Weight: 5.74 kg  
 Scx: 0.077 m²



TLG\_CTEQ\_F\_SMTP36LEDPDB.jpg



TLG\_CETQ\_M\_S.wmf

This product contains light sources of energy efficiency class D.