


IQ Wave SP


Comfort without compromise for office & education. A logical range extension to the IQ wave family for surface and suspended

- Design: Form follows function. Simple and flowing lines create a modern but simplistic aesthetic, perfect for an elegant office interior.
- Optics: Innovative and Thorn patented MV tech optic offers excellent uniformity and glare control, direct/indirect light for illuminance on faces and walls to encourage a comfortable, communicative working environment.
- Controls: Integrated sensors allow you to create flexible control systems suited to your needs. Wireless solution controlled via App with Bluetooth® 4.x basicDim Wireless. Also available are integrated PIR and microwave sensors.
- Additional sensor, controls, wireless, wiring and mounting options are available through myProduct
- Versions adapted for mounting onto Contus trunking available.

Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.







96629272

Material/Finish

Frame and end caps: polycarbonate.

Diffuser and body: polycarbonate, aluminium heatsink.

Gear tray: pre-coated white steel with polycarbonate endcaps.

Contus adapter: pre-coated roll form steel, white (similar to RAL9016).

Installation/Mounting

Suspended:

Suitable for suspension with included Y suspension Kit and pre-assembled power cord.

Surface:

Suitable for direct surface or BESA mounting, central or end-cap cable entries.

Continuous run:

For Through Wiring on a continuous run – you will require to use myProduct to order the Through Wiring version (see TW in Variants). For continuous run please also order connector kit to connect standard or through wiring luminaires together. Contus Trunking:

Versions adapted for Contus trunking come pre-assembled, ready to fit quickly and easily with twist & lock mechanical/electrical connections.



IQ Wave SP

Ordering Guide Variants available via myProduct

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
IQ Wave Surface, dimmable				
IQ SURF S LED2600-840 HFIX	LED		4,1	96628941
IQ SURF S LED4250-840 HFIX	LED		4,1	96628943
IQ SURF L LED4250-840 HFIX	LED		5	96628945
IQ SURF L LED4900-840 HFIX	LED		5	96628947
IQ SURF L LED6700-840 HFIX	LED		5	96628949
IQ Wave Surface, dimmable (variants)				
IQ SURF L LED4250-840 HFIX ASY	LED		5,1	96629836
IQ SURF L LED4900-840 BC	LED		5,1	96631045
IQ Wave Surface				
IQ SURF S LED2600-840 HF WH	LED		4	96629267
IQ SURF S LED4250-840 HF WH	LED		4	96629269
IQ SURF L LED4250-840 HF WH	LED		4,9	96629271
IQ SURF L LED4900-840 HF WH	LED		4,9	96629273
IQ SURF L LED6700-840 HF WH	LED		4,9	96629275
IQ SURF L LED6700-840 HF ASY	LED		4,9	96629309
IQ Wave Surface, sensor				
IQ SURF L LED6700-840 HFSX	LED		5,1	96629305
IQ Wave Suspended, dimmable				
IQ SUSP S LED6700-840 HFIX ML5 WH	LED		4,4	96628957
IQ SUSP S LED2600-840 HFIX ML5	LED		4,4	96628951
IQ SUSP S LED4250-840 HFIX ML5 WH	LED		4,4	96628953
IQ SUSP S LED4900-840 HFIX ML5	LED		4,4	96628955
IQ Wave Suspended, dimmable (variants)				
IQ SUSP S LED4900-840 BC ML3	LED		4,5	96631046
IQ SUSP S LED6700-840 BC ML3	LED		4,5	96631047
IQ Wave Suspended, Contus				
IQ SUSP S LED2600-840 HF CONT WH	LED		4,12	96637140
IQ SUSP S LED4250-840 HF CONT WH	LED		4,12	96637141
IQ SUSP S LED4900-840 HF CONT WH	LED		4,12	96637142
IQ SUSP S LED6700-840 HF CONT WH	LED		4,12	96637143
IQ Wave Suspended, basicDIM, emergency				
IQ SUSP S LED6700-840 BC E3 ML4	LED		5	92902253
IQ Wave Suspended				
IQ SUSP S LED2600-840 HF ML3 WH	LED		4,3	96629277
IQ SUSP S LED4250-840 HF ML3 WH	LED		4,3	96629279
IQ SUSP S LED4900-840 HF ML3 WH	LED		4,3	96629281
IQ SUSP S LED6700-840 HF ML3 WH	LED		4,3	96629283
IQ Wave Suspended, through wiring				
IQ SUSP S LED2600-840 HF TW6	LED		5,2	92901666





IQ Wave SP

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
IQ Wave Accessories				
REMOTECONTROL IR6			0,019	28000647
IQ SUSP connection kit standard WH			0,6	96629284
IQ SURF connection kit standard WH			0,5	96629286